WINTER-PROOF PARKING

The cold season puts very special demands on a motorhome. Because the low temperatures require special measures if you want to put your MORELO First Class motorhome into a well-deserved hibernation. We have put together some useful tips for you as follows.

Water tank

- open waste water (drain water completely)
 open black water (drain water completely)
 open fresh water (drain water completely)
 - 4. open 100 l drain (drain water completely)
 - 5. open flushing units (drain water completely)

Emptying the tank

The vehicle should be on a level surface when emptying the tank, if possible,
it should be tilted to the emptying side using the air suspension or
the hydraulic levelling jacks.

Water system, pump and filter

- 1. switch off water pump on control panel
- 2. open the yellow drain valve in front of the water distribution system
- 3. open yellow drain valve in front of heating boiler
- 4. drain water pump and pipes
- remove residual water from the filter housing, dry the filter and put it back
- **6.** remove the filled Carawater water filter and store it in a warm place. Then install the empty dummy.

Optional for Alde-Flow

- 1. open yellow drain valve in front of ALDE-Flow
- 2. drain water from the heating boiler

Optional with Scheer heating

1. empty the plate heat exchanger



WINTER-PROOF PARKING

 Cassette toilet remove the cassette and empty it completely close the cassette and reinsert it 	
Water pipes and taps open all taps to the middle position and let them run empty	
 kitchen sink 	
2. washbasin	
3. shower	
Flush siphons with antifreeze	
1. kitchen sink	
2. washbasin	
3. shower	
To avoid corrosion stains, remove excess antifreeze immediately!	
Fixed tank toilet	
1. flush siphon / bend with antifreeze	
Oriental shower option	
1. open water tap at the mixer tap	
2. take the shower head out of the holder, pull out the hose	completely 🗌
and bring it to the lowest point3. press the button on the shower head, keep it pressed and	
J. press the button on the shower head, keep it pressed and	
Optional outside shower	
1. open water tap at the mixer tap	
2. take the shower head out of the holder, pull out the hose	completely
and bring it to the lowest point3. press the button on the shower head, keep it pressed and	
J. press the button on the shower head, keep it pressed and	
The taps remain open throughout the winter!	



WINTER-PROOF PARKING

General

- 1. remove snow and ice from the roof before driving off
- 2. treat rubber seals with rubber care
- **3.** release the handbrake if the vehicle is parked for a longer period of time and secure the vehicle against rolling away
- **4.** check the vehicle weekly to see if the main switch has tripped due to power failure, power fluctuation on shore power

If the vehicle is connected to shore power

- 1. set heating to 1 kW or gas to 15 °C
- **2.** deactivate domestic water
- **3.** set the inverter to 10 A

NOTES

